

5.6 Conditions to avoid (polymerization) High humidity and prolonged heat greater than 60° C

SECTION VI – Health Hazard Data

6.1 Primary routes(s) of entry:	Inhalation?: Yes Skin?: No Ingestion?: Yes
6.2 Health Hazards (acute and chronic):	Acute: Transitory upper respiratory irritation or eye irritation Chronic: Inhalation of crystalline silica has been classified by IARC as carcinogenic for humans (Group I). Inhalation of crystalline silica is known as a cause of silicosis, a non-cancerous lung disease caused by excessive exposure to crystalline silica. Respirable dust from this product may contain up to 52% free crystalline silica. As such it represents a risk to the respiratory system. Long term, unprotected exposure to dust levels in excess of the TLV or PEL may cause lung disease (silicosis).
6.3 Carcinogenicity:	NTP?: Proposed IARC monographs: Yes (Group 1) OSHA Regulated?: Yes
6.4 Signs and symptoms of exposure:	Inhalation: Irritation and soreness in throat and nose. In extreme exposures some congestion may occur. Eyes: temporary irritation or inflammation. Not hazardous when ingested.
6.5 Medical conditions generally aggravated by exposure:	Pre-existing upper respiratory and lung diseases such as but not limited to bronchitis, emphysema, and asthma. Target organs: Lungs and eyes.
6.6 Emergency First aid procedures:	Remove to fresh air. Drink water to clear throat and blow nose to evacuate dust. For eyes flush with copious amounts of water for 15 minutes. If irritation persists consult a physician.

SECTION VII – Precautions for Safe Handling

7.1 Steps to be taken in case material is released or spilled:	Vacuum dust with equipment fitted with a HEPA filter. Use dust suppression such as water if sweeping is necessary. Sweep up spilled material and place in closed containers for disposal.
7.2 Waste Disposal methods:	Dispose of in accordance with Federal, State and Local regulations
7.3 Precautions to be taken in handling and storage:	Minimize dust generation and accumulation. Avoid breathing dust, avoid contact with eyes. Reclose packages and containers immediately. Continue to follow all MSDS/label warnings when handling empty containers. Observe normal warehouse handling procedures. Store in a cool dry area. Store away from foodstuffs and beverages.
7.4 Other precaution:	The avoidance of any air contaminant is always a recommended practice. Adherence to work place ventilation standards is an assurance of general personal health and comfort.

SECTION VII – Control Measure / Personal Protection

8.1 Respiratory protection:	Recommended NIOSH approved nuisance dust mask. <10X PEL, use 3M 9900; <100X PEL, use MSA Ultra-twin with H Filter; <200X PEL, use MSA 01-00-06 with type C supplied for air unit (continuous flow mode); or equivalent.
8.2 Ventilation:	Use sufficient natural or mechanical ventilation to keep dust level below PEL.
8.3 Protective gloves:	Rubber gloves
8.4 Eye protection:	Goggles or safety glasses with shields
8.5 Other protective clothing or equipment:	Rubber apron
8.6 Work/Hygienic practices:	Avoid dusting when in use. Observe normal care when working with chemicals.

NFPA – National Fire Protection Association
N/A – Not Applicable
N/E – Not Established

NFPA HAZARD CLASSIFICATIONS	
Health	2
Flammability	0
Reactivity	0

Specific Hazard	N/A
-----------------	-----

ARTMOLDS 1004 6/15/2003

